CBJYJ2022-001(0355) REV.02 Effective Date: 2022.3.15

OD	Weight	Wall Th	Grade	API Drift	Connection
3.500in	6.50lb/ft	0.170in	CB140V	3.035in	CBS3

PIPE BODY PROPERTIES	
Nominal OD	3.500 in
Nominal ID	3.160 in
Nominal Wall Thickness	0.170 in
Minimum Wall Thickness	87.5 %
Nominal Weight(API)	6.50 lb/ft
Plain End Weight	6.05 lb/ft
Drift	3.035 in
Grade Type	API 5CT
Minimum Yield Strength	140 ksi
Maximum Yield Strength	170 ksi
Minimum Ultimate Tensile Strength	150 ksi
Pipe Body Yield Strength	249 klb
Internal Yield Strength	11,900 psi
Collapse Pressure	5,740 psi

CONNECTION PROPERTIES	
Connection Type	Premium Thread&Coupled
Nominal Connection OD	3.846 in
Nominal Connection ID	3.104 in
Make-up Loss	3.229 in
Coupling Length	7.559 in
Tension Efficiency	100% of Pipe Body
Compression Efficiency	100% of Pipe Body
Internal Pressure Efficiency	100% of Pipe Body
External Pressure Efficiency	100% of Pipe Body

JOINT PERFORMANCES	
Tensile Strength	249 klb
Compression Strength	249 klb
Internal Pressure Resistance	11,900 psi
External Pressure Resistance	5,740 psi
Maximum Bending	30 °/100 ft
Maximum Load on Coupling Face	169 klb

FIELD TORQUE VALUES	
Friction Coefficient	1
Min. Make-up torque	1,640 ft-lb
Opti. Make-up torque	1,820 ft-lb
Max. Make-up torque	1,990 ft-lb
Min. Shoulder torque	90 ft-lb
Max. Shoulder torque	1,450 ft-lb
Min. Delta Turn	0.010 turns
Max. Delta Turn	0.120 turns

Generated on 14/11/2026