

CBJY2022-001(0336) REV.02 Effective Date: 2022.3.15

OD	Weight	Wall Th	Grade	API Drift	Connection
3.500in	7.70lb/ft	0.216in	P110	2.943in	CBS3

PIPE BODY PROPERTIES	
Nominal OD	3.500 in
Nominal ID	3.068 in
Nominal Wall Thickness	0.216 in
Minimum Wall Thickness	87.5 %
Nominal Weight(API)	7.70 lb/ft
Plain End Weight	7.58 lb/ft
Drift	2.943 in
Grade Type	API 5CT
Minimum Yield Strength	110 ksi
Maximum Yield Strength	140 ksi
Minimum Ultimate Tensile Strength	125 ksi
Pipe Body Yield Strength	245 klb
Internal Yield Strength	11,880 psi
Collapse Pressure	9,740 psi

CONNECTION PROPERTIES	
Connection Type	Premium Thread&Coupled
Nominal Connection OD	3.907 in
Nominal Connection ID	3.022 in
Make-up Loss	3.229 in
Coupling Length	7.559 in
Tension Efficiency	100% of Pipe Body
Compression Efficiency	100% of Pipe Body
Internal Pressure Efficiency	100% of Pipe Body
External Pressure Efficiency	100% of Pipe Body

JOINT PERFORMANCES	
Tensile Strength	245 klb
Compression Strength	245 klb
Internal Pressure Resistance	11,880 psi
External Pressure Resistance	9,740 psi
Maximum Bending	30 °/100 ft
Maximum Load on Coupling Face	173 klb

FIELD TORQUE VALUES	
Friction Coefficient	1
Min. Make-up torque	2,290 ft-lb
Opti. Make-up torque	2,530 ft-lb
Max. Make-up torque	2,770 ft-lb
Min. Shoulder torque	130 ft-lb
Max. Shoulder torque	2,030 ft-lb
Min. Delta Turn	0.010 turns
Max. Delta Turn	0.120 turns

Generated on 10/06/2026