

CBJY2022-001(0346) REV.02 Effective Date: 2022.3.15

OD	Weight	Wall Th	Grade	API Drift	Connection
3.500in	7.70lb/ft	0.216in	Q125	2.943in	CBS3

PIPE BODY PROPERTIES	
Nominal OD	3.500 in
Nominal ID	3.068 in
Nominal Wall Thickness	0.216 in
Minimum Wall Thickness	87.5 %
Nominal Weight(API)	7.70 lb/ft
Plain End Weight	7.58 lb/ft
Drift	2.943 in
Grade Type	API 5CT
Minimum Yield Strength	125 ksi
Maximum Yield Strength	150 ksi
Minimum Ultimate Tensile Strength	135 ksi
Pipe Body Yield Strength	279 klb
Internal Yield Strength	13,500 psi
Collapse Pressure	10,500 psi

CONNECTION PROPERTIES	
Connection Type	Premium Thread&Coupled
Nominal Connection OD	3.907 in
Nominal Connection ID	3.022 in
Make-up Loss	3.229 in
Coupling Length	7.559 in
Tension Efficiency	100% of Pipe Body
Compression Efficiency	100% of Pipe Body
Internal Pressure Efficiency	100% of Pipe Body
External Pressure Efficiency	100% of Pipe Body

JOINT PERFORMANCES	
Tensile Strength	279 klb
Compression Strength	279 klb
Internal Pressure Resistance	13,500 psi
External Pressure Resistance	10,500 psi
Maximum Bending	30 °/100 ft
Maximum Load on Coupling Face	179 klb

FIELD TORQUE VALUES	
Friction Coefficient	1
Min. Make-up torque	2,430 ft-lb
Opti. Make-up torque	2,690 ft-lb
Max. Make-up torque	2,940 ft-lb
Min. Shoulder torque	130 ft-lb
Max. Shoulder torque	2,150 ft-lb
Min. Delta Turn	0.010 turns
Max. Delta Turn	0.120 turns

Generated on 10/06/2026