

Version number:REV.02

OD	Weight	Wall Th	Grade	API Drift	Connection
3.500in	12.70lb/ft	0.375in	T95	2.625in	CBS3

PIPE BODY PROPERTIES	
Nominal OD	3.500 in
Nominal ID	2.750 in
Nominal Wall Thickness	0.375 in
Minimum Wall Thickness	87.5 %
Nominal Weight(API)	12.70 lb/ft
Plain End Weight	12.53 lb/ft
Drift	2.625 in
Grade Type	API 5CT
Minimum Yield Strength	95 ksi
Maximum Yield Strength	110 ksi
Minimum Ultimate Tensile Strength	105 ksi
Pipe Body Yield Strength	350 klb
Internal Yield Strength	17,810 psi
Collapse Pressure	18,190 psi

CONNECTION PROPERTIES	
Connection Type	Premium Thread&Coupled
Nominal Connection OD	4.098 in
Nominal Connection ID	2.707 in
Make-up Loss	4.017 in
Coupling Length	9.016 in
Tension Efficiency	100% of Pipe Body
Compression Efficiency	100% of Pipe Body
Internal Pressure Efficiency	100% of Pipe Body
External Pressure Efficiency	100% of Pipe Body

JOINT PERFORMANCES	
Tensile Strength	350 klb
Compression Strength	350 klb
Internal Pressure Resistance	17,810 psi
External Pressure Resistance	18,190 psi
Maximum Bending	30 °/100 ft
Maximum Load on Coupling Face	266 klb

FIELD TORQUE VALUES	
Min. Make-up torque	5,390 ft-lb
Opti. Make-up torque	5,980 ft-lb
Max. Make-up torque	6,570 ft-lb
Min. Shoulder torque	300 ft-lb
Max. Shoulder torque	4,780 ft-lb
Min. Delta Turn	0.010 turns
Max. Delta Turn	0.120 turns

Generated on 24/02/2025