

CBJY2022-001(0454) REV.02 Effective Date: 2022.3.15

|         |           |         |       |           |            |
|---------|-----------|---------|-------|-----------|------------|
| OD      | Weight    | Wall Th | Grade | API Drift | Connection |
| 4.000in | 8.20lb/ft | 0.190in | T95   | 3.495in   | CBS3       |

| PIPE BODY PROPERTIES              |            |
|-----------------------------------|------------|
| Nominal OD                        | 4.000 in   |
| Nominal ID                        | 3.620 in   |
| Nominal Wall Thickness            | 0.190 in   |
| Minimum Wall Thickness            | 87.5 %     |
| Nominal Weight(API)               | 8.20 lb/ft |
| Plain End Weight                  | 7.74 lb/ft |
| Drift                             | 3.495 in   |
| Grade Type                        | API 5CT    |
| Minimum Yield Strength            | 95 ksi     |
| Maximum Yield Strength            | 110 ksi    |
| Minimum Ultimate Tensile Strength | 105 ksi    |
| Pipe Body Yield Strength          | 216 klb    |
| Internal Yield Strength           | 7,900 psi  |
| Collapse Pressure                 | 4,640 psi  |

| CONNECTION PROPERTIES        |                        |
|------------------------------|------------------------|
| Connection Type              | Premium Thread&Coupled |
| Nominal Connection OD        | 4.362 in               |
| Nominal Connection ID        | 3.567 in               |
| Make-up Loss                 | 3.356 in               |
| Coupling Length              | 7.717 in               |
| Tension Efficiency           | 100% of Pipe Body      |
| Compression Efficiency       | 100% of Pipe Body      |
| Internal Pressure Efficiency | 100% of Pipe Body      |
| External Pressure Efficiency | 100% of Pipe Body      |

| JOINT PERFORMANCES            |             |
|-------------------------------|-------------|
| Tensile Strength              | 216 klb     |
| Compression Strength          | 216 klb     |
| Internal Pressure Resistance  | 7,900 psi   |
| External Pressure Resistance  | 4,640 psi   |
| Maximum Bending               | 30 °/100 ft |
| Maximum Load on Coupling Face | 150 klb     |

| FIELD TORQUE VALUES  |             |
|----------------------|-------------|
| Friction Coefficient | 1           |
| Min. Make-up torque  | 2,180 ft-lb |
| Opti. Make-up torque | 2,420 ft-lb |
| Max. Make-up torque  | 2,660 ft-lb |
| Min. Shoulder torque | 120 ft-lb   |
| Max. Shoulder torque | 1,940 ft-lb |
| Min. Delta Turn      | 0.010 turns |
| Max. Delta Turn      | 0.120 turns |

Generated on 07/07/2026