

CBJY2022-001(1005) REV.02 Effective Date: 2022.3.15

OD	Weight	Wall Th	Grade	API Drift	Connection
7.000in	26.00lb/ft	0.362in	L80-1	6.151in	CBS3

PIPE BODY PROPERTIES	
Nominal OD	7.000 in
Nominal ID	6.276 in
Nominal Wall Thickness	0.362 in
Minimum Wall Thickness	87.5 %
Nominal Weight(API)	26.00 lb/ft
Plain End Weight	25.69 lb/ft
Drift	6.151 in
Grade Type	API 5CT
Minimum Yield Strength	80 ksi
Maximum Yield Strength	95 ksi
Minimum Ultimate Tensile Strength	95 ksi
Pipe Body Yield Strength	604 klb
Internal Yield Strength	7,240 psi
Collapse Pressure	5,410 psi

CONNECTION PROPERTIES	
Connection Type	Premium Thread&Coupled
Nominal Connection OD	7.644 in
Nominal Connection ID	6.325 in
Make-up Loss	4.973 in
Coupling Length	11.929 in
Tension Efficiency	100% of Pipe Body
Compression Efficiency	60% of Pipe Body
Internal Pressure Efficiency	100% of Pipe Body
External Pressure Efficiency	100% of Pipe Body

JOINT PERFORMANCES	
Tensile Strength	604 klb
Compression Strength	362 klb
Internal Pressure Resistance	7,240 psi
External Pressure Resistance	5,410 psi
Maximum Bending	30 °/100 ft
Maximum Load on Coupling Face	447 klb

FIELD TORQUE VALUES	
Friction Coefficient	1
Min. Make-up torque	7,690 ft-lb
Opti. Make-up torque	8,490 ft-lb
Max. Make-up torque	9,280 ft-lb
Min. Shoulder torque	420 ft-lb
Max. Shoulder torque	6,790 ft-lb
Min. Delta Turn	0.010 turns
Max. Delta Turn	0.120 turns

Generated on 06/07/2026