

CBJY2022-001(0876) REV.02 Effective Date: 2022.3.15

OD	Weight	Wall Th	Grade	API Drift	Connection
5.500in	17.00lb/ft	0.304in	C110	4.767in	CBS3

PIPE BODY PROPERTIES	
Nominal OD	5.500 in
Nominal ID	4.892 in
Nominal Wall Thickness	0.304 in
Minimum Wall Thickness	87.5 %
Nominal Weight(API)	17.00 lb/ft
Plain End Weight	16.89 lb/ft
Drift	4.767 in
Grade Type	API 5CT
Minimum Yield Strength	110 ksi
Maximum Yield Strength	120 ksi
Minimum Ultimate Tensile Strength	115 ksi
Pipe Body Yield Strength	546 klb
Internal Yield Strength	10,640 psi
Collapse Pressure	7,480 psi

CONNECTION PROPERTIES	
Connection Type	Premium Thread&Coupled
Nominal Connection OD	6.071 in
Nominal Connection ID	4.896 in
Make-up Loss	4.579 in
Coupling Length	11.142 in
Tension Efficiency	100% of Pipe Body
Compression Efficiency	60% of Pipe Body
Internal Pressure Efficiency	100% of Pipe Body
External Pressure Efficiency	100% of Pipe Body

JOINT PERFORMANCES	
Tensile Strength	546 klb
Compression Strength	327 klb
Internal Pressure Resistance	10,640 psi
External Pressure Resistance	7,480 psi
Maximum Bending	30 °/100 ft
Maximum Load on Coupling Face	358 klb

FIELD TORQUE VALUES	
Friction Coefficient	1
Min. Make-up torque	5,950 ft-lb
Opti. Make-up torque	6,580 ft-lb
Max. Make-up torque	6,890 ft-lb
Min. Shoulder torque	330 ft-lb
Max. Shoulder torque	5,260 ft-lb
Min. Delta Turn	0.010 turns
Max. Delta Turn	0.120 turns

Generated on 26/05/2026