

CBJYJ2022-001 (002) REV.02 Effective Date: 2022.3.15

OD	Weight	Wall Th	Grade	API Drift	Connection
7.000in	35.00lb/ft	0.498in	T95	5.879in	CBS3

PIPE BODY PROPERTIES	
Nominal OD	7.000 in
Nominal ID	6.004 in
Nominal Wall Thickness	0.498 in
Minimum Wall Thickness	87.5 %
Nominal Weight(API)	35.00 lb/ft
Plain End Weight	34.61 lb/ft
Drift	5.879 in
Grade Type	API 5CT
Minimum Yield Strength	95 ksi
Maximum Yield Strength	110 ksi
Minimum Ultimate Tensile Strength	105 ksi
Pipe Body Yield Strength	966 klb
Internal Yield Strength	11,830 psi
Collapse Pressure	11,650 psi

CONNECTION PROPERTIES	
Connection Type	Premium Thread&Coupled
Nominal Connection OD	7.852 in
Nominal Connection ID	6.161 in
Make-up Loss	4.973 in
Coupling Length	11.929 in
Tension Efficiency	100% of Pipe Body
Compression Efficiency	60% of Pipe Body
Internal Pressure Efficiency	100% of Pipe Body
External Pressure Efficiency	100% of Pipe Body

JOINT PERFORMANCES	
Tensile Strength	966 klb
Compression Strength	580 klb
Internal Pressure Resistance	11,830 psi
External Pressure Resistance	11,650 psi
Maximum Bending	30 °/100 ft
Maximum Load on Coupling Face	772 klb

FIELD TORQUE VALUES	
Min. Make-up torque	13,820 ft-lb
Opti. Make-up torque	15,350 ft-lb
Max. Make-up torque	16,890 ft-lb
Min. Shoulder torque	770 ft-lb
Max. Shoulder torque	12,280 ft-lb
Min. Delta Turn	0.010 turns
Max. Delta Turn	0.120 turns

Generated on 05/04/2025