

CBJY2022-001(0537) REV.02 Effective Date: 2022.3.15

OD	Weight	Wall Th	Grade	API Drift	Connection
4.500in	13.50lb/ft	0.290in	N80Q	3.795in	CBS3

PIPE BODY PROPERTIES	
Nominal OD	4.500 in
Nominal ID	3.920 in
Nominal Wall Thickness	0.290 in
Minimum Wall Thickness	87.5 %
Nominal Weight(API)	13.50 lb/ft
Plain End Weight	13.05 lb/ft
Drift	3.795 in
Grade Type	API 5CT
Minimum Yield Strength	80 ksi
Maximum Yield Strength	110 ksi
Minimum Ultimate Tensile Strength	100 ksi
Pipe Body Yield Strength	307 klb
Internal Yield Strength	9,020 psi
Collapse Pressure	8,540 psi

CONNECTION PROPERTIES	
Connection Type	Premium Thread&Coupled
Nominal Connection OD	5.042 in
Nominal Connection ID	3.877 in
Make-up Loss	3.419 in
Coupling Length	7.953 in
Tension Efficiency	100% of Pipe Body
Compression Efficiency	100% of Pipe Body
Internal Pressure Efficiency	100% of Pipe Body
External Pressure Efficiency	100% of Pipe Body

JOINT PERFORMANCES	
Tensile Strength	307 klb
Compression Strength	307 klb
Internal Pressure Resistance	9,020 psi
External Pressure Resistance	8,540 psi
Maximum Bending	30 °/100 ft
Maximum Load on Coupling Face	245 klb

FIELD TORQUE VALUES	
Friction Coefficient	1
Min. Make-up torque	4,500 ft-lb
Opti. Make-up torque	5,020 ft-lb
Max. Make-up torque	5,540 ft-lb
Min. Shoulder torque	250 ft-lb
Max. Shoulder torque	4,010 ft-lb
Min. Delta Turn	0.010 turns
Max. Delta Turn	0.120 turns

Generated on 06/07/2026