

CBJY2022-001(0978) REV.02 Effective Date: 2022.3.15

OD	Weight	Wall Th	Grade	API Drift	Connection
6.625in	28.00lb/ft	0.417in	Q125	5.666in	CBS3

PIPE BODY PROPERTIES	
Nominal OD	6.625 in
Nominal ID	5.791 in
Nominal Wall Thickness	0.417 in
Minimum Wall Thickness	87.5 %
Nominal Weight(API)	28.00 lb/ft
Plain End Weight	27.67 lb/ft
Drift	5.666 in
Grade Type	API 5CT
Minimum Yield Strength	125 ksi
Maximum Yield Strength	150 ksi
Minimum Ultimate Tensile Strength	135 ksi
Pipe Body Yield Strength	1,017 klb
Internal Yield Strength	13,770 psi
Collapse Pressure	10,990 psi

CONNECTION PROPERTIES	
Connection Type	Premium Thread&Coupled
Nominal Connection OD	7.390 in
Nominal Connection ID	5.931 in
Make-up Loss	4.624 in
Coupling Length	11.260 in
Tension Efficiency	100% of Pipe Body
Compression Efficiency	60% of Pipe Body
Internal Pressure Efficiency	100% of Pipe Body
External Pressure Efficiency	100% of Pipe Body

JOINT PERFORMANCES	
Tensile Strength	1,017 klb
Compression Strength	610 klb
Internal Pressure Resistance	13,770 psi
External Pressure Resistance	10,990 psi
Maximum Bending	30 °/100 ft
Maximum Load on Coupling Face	838 klb

FIELD TORQUE VALUES	
Friction Coefficient	1
Min. Make-up torque	11,230 ft-lb
Opti. Make-up torque	12,470 ft-lb
Max. Make-up torque	13,710 ft-lb
Min. Shoulder torque	620 ft-lb
Max. Shoulder torque	9,980 ft-lb
Min. Delta Turn	0.010 turns
Max. Delta Turn	0.120 turns

Generated on 07/07/2026