

CBJY2022-001(1076) REV.02 Effective Date: 2022.3.15

OD	Weight	Wall Th	Grade	API Drift	Connection
7.000in	32.00lb/ft	0.453in	Q125	5.969in	CBS3

PIPE BODY PROPERTIES	
Nominal OD	7.000 in
Nominal ID	6.094 in
Nominal Wall Thickness	0.453 in
Minimum Wall Thickness	87.5 %
Nominal Weight(API)	32.00 lb/ft
Plain End Weight	31.70 lb/ft
Drift	5.969 in
Grade Type	API 5CT
Minimum Yield Strength	125 ksi
Maximum Yield Strength	150 ksi
Minimum Ultimate Tensile Strength	135 ksi
Pipe Body Yield Strength	1,165 klb
Internal Yield Strength	14,160 psi
Collapse Pressure	11,710 psi

CONNECTION PROPERTIES	
Connection Type	Premium Thread&Coupled
Nominal Connection OD	7.787 in
Nominal Connection ID	6.242 in
Make-up Loss	4.973 in
Coupling Length	11.929 in
Tension Efficiency	100% of Pipe Body
Compression Efficiency	60% of Pipe Body
Internal Pressure Efficiency	100% of Pipe Body
External Pressure Efficiency	100% of Pipe Body

JOINT PERFORMANCES	
Tensile Strength	1,165 klb
Compression Strength	699 klb
Internal Pressure Resistance	14,160 psi
External Pressure Resistance	11,710 psi
Maximum Bending	30 °/100 ft
Maximum Load on Coupling Face	916 klb

FIELD TORQUE VALUES	
Friction Coefficient	1
Min. Make-up torque	13,520 ft-lb
Opti. Make-up torque	14,980 ft-lb
Max. Make-up torque	16,440 ft-lb
Min. Shoulder torque	750 ft-lb
Max. Shoulder torque	11,990 ft-lb
Min. Delta Turn	0.010 turns
Max. Delta Turn	0.120 turns

Generated on 07/07/2026