CBJYJ2022-001(0806) REV.02 Effective Date: 2022.3.15

OD	Weight	Wall Th	Grade	API Drift	Connection
5.500in	26.00lb/ft	0.476in	N80Q	4.423in	CBS3

PIPE BODY PROPERTIES	
Nominal OD	5.500 in
Nominal ID	4.548 in
Nominal Wall Thickness	0.476 in
Minimum Wall Thickness	87.5 %
Nominal Weight(API)	26.00 lb/ft
Plain End Weight	25.56 lb/ft
Drift	4.423 in
Grade Type	API 5CT
Minimum Yield Strength	80 ksi
Maximum Yield Strength	110 ksi
Minimum Ultimate Tensile Strength	100 ksi
Pipe Body Yield Strength	601 klb
Internal Yield Strength	12,120 psi
Collapse Pressure	12,650 psi

CONNECTION PROPERTIES	
Connection Type	Premium Thread&Coupled
Nominal Connection OD	6.283 in
Nominal Connection ID	4.691 in
Make-up Loss	4.579 in
Coupling Length	11.142 in
Tension Efficiency	100% of Pipe Body
Compression Efficiency	60% of Pipe Body
Internal Pressure Efficiency	100% of Pipe Body
External Pressure Efficiency	100% of Pipe Body

JOINT PERFORMANCES	
Tensile Strength	601 klb
Compression Strength	361 klb
Internal Pressure Resistance	12,120 psi
External Pressure Resistance	12,650 psi
Maximum Bending	30 °/100 ft
Maximum Load on Coupling Face	467 klb

FIELD TORQUE VALUES	
Friction Coefficient	1
Min. Make-up torque	9,900 ft-lb
Opti. Make-up torque	11,000 ft-lb
Max. Make-up torque	12,090 ft-lb
Min. Shoulder torque	550 ft-lb
Max. Shoulder torque	8,800 ft-lb
Min. Delta Turn	0.010 turns
Max. Delta Turn	0.120 turns

Generated on 22/11/2026