CBJYJ2022-001(0741) REV.02 Effective Date: 2022.3.15

OD	Weight	Wall Th	Grade	API Drift	Connection
5.000in	20.30lb/ft	0.408in	T95	4.059in	CBS3

PIPE BODY PROPERTIES	
Nominal OD	5.000 in
Nominal ID	4.184 in
Nominal Wall Thickness	0.408 in
Minimum Wall Thickness	87.5 %
Nominal Weight(API)	20.30 lb/ft
Plain End Weight	20.03 lb/ft
Drift	4.059 in
Grade Type	API 5CT
Minimum Yield Strength	95 ksi
Maximum Yield Strength	110 ksi
Minimum Ultimate Tensile Strength	105 ksi
Pipe Body Yield Strength	559 klb
Internal Yield Strength	13,570 psi
Collapse Pressure	14,240 psi

CONNECTION PROPERTIES	
Connection Type	Premium Thread&Coupled
Nominal Connection OD	5.669 in
Nominal Connection ID	4.307 in
Make-up Loss	4.388 in
Coupling Length	10.787 in
Tension Efficiency	100% of Pipe Body
Compression Efficiency	60% of Pipe Body
Internal Pressure Efficiency	100% of Pipe Body
External Pressure Efficiency	100% of Pipe Body

JOINT PERFORMANCES	
Tensile Strength	559 klb
Compression Strength	336 klb
Internal Pressure Resistance	13,570 psi
External Pressure Resistance	14,240 psi
Maximum Bending	30 °/100 ft
Maximum Load on Coupling Face	409 klb

FIELD TORQUE VALUES	
Friction Coefficient	1
Min. Make-up torque	7,700 ft-lb
Opti. Make-up torque	8,520 ft-lb
Max. Make-up torque	9,340 ft-lb
Min. Shoulder torque	430 ft-lb
Max. Shoulder torque	6,810 ft-lb
Min. Delta Turn	0.010 turns
Max. Delta Turn	0.120 turns

Generated on 22/11/2026