

CBJY2022-001(0741) REV.02 Effective Date: 2022.3.15

| OD      | Weight     | Wall Th | Grade | API Drift | Connection |
|---------|------------|---------|-------|-----------|------------|
| 5.000in | 20.30lb/ft | 0.408in | T95   | 4.059in   | CBS3       |

| PIPE BODY PROPERTIES              |             |
|-----------------------------------|-------------|
| Nominal OD                        | 5.000 in    |
| Nominal ID                        | 4.184 in    |
| Nominal Wall Thickness            | 0.408 in    |
| Minimum Wall Thickness            | 87.5 %      |
| Nominal Weight(API)               | 20.30 lb/ft |
| Plain End Weight                  | 20.03 lb/ft |
| Drift                             | 4.059 in    |
| Grade Type                        | API 5CT     |
| Minimum Yield Strength            | 95 ksi      |
| Maximum Yield Strength            | 110 ksi     |
| Minimum Ultimate Tensile Strength | 105 ksi     |
| Pipe Body Yield Strength          | 559 klb     |
| Internal Yield Strength           | 13,570 psi  |
| Collapse Pressure                 | 14,240 psi  |

| CONNECTION PROPERTIES        |                        |
|------------------------------|------------------------|
| Connection Type              | Premium Thread&Coupled |
| Nominal Connection OD        | 5.669 in               |
| Nominal Connection ID        | 4.307 in               |
| Make-up Loss                 | 4.388 in               |
| Coupling Length              | 10.787 in              |
| Tension Efficiency           | 100% of Pipe Body      |
| Compression Efficiency       | 60% of Pipe Body       |
| Internal Pressure Efficiency | 100% of Pipe Body      |
| External Pressure Efficiency | 100% of Pipe Body      |

| JOINT PERFORMANCES            |             |
|-------------------------------|-------------|
| Tensile Strength              | 559 klb     |
| Compression Strength          | 336 klb     |
| Internal Pressure Resistance  | 13,570 psi  |
| External Pressure Resistance  | 14,240 psi  |
| Maximum Bending               | 30 °/100 ft |
| Maximum Load on Coupling Face | 409 klb     |

| FIELD TORQUE VALUES  |             |
|----------------------|-------------|
| Friction Coefficient | 1           |
| Min. Make-up torque  | 7,700 ft-lb |
| Opti. Make-up torque | 8,520 ft-lb |
| Max. Make-up torque  | 9,340 ft-lb |
| Min. Shoulder torque | 430 ft-lb   |
| Max. Shoulder torque | 6,810 ft-lb |
| Min. Delta Turn      | 0.010 turns |
| Max. Delta Turn      | 0.120 turns |

Generated on 03/05/2026