

CBJY2022-001(1077) REV.02 Effective Date: 2022.3.15

OD	Weight	Wall Th	Grade	API Drift	Connection
7.000in	35.00lb/ft	0.498in	Q125	5.879in	CBS3

PIPE BODY PROPERTIES	
Nominal OD	7.000 in
Nominal ID	6.004 in
Nominal Wall Thickness	0.498 in
Minimum Wall Thickness	87.5 %
Nominal Weight(API)	35.00 lb/ft
Plain End Weight	34.61 lb/ft
Drift	5.879 in
Grade Type	API 5CT
Minimum Yield Strength	125 ksi
Maximum Yield Strength	150 ksi
Minimum Ultimate Tensile Strength	135 ksi
Pipe Body Yield Strength	1,272 klb
Internal Yield Strength	15,560 psi
Collapse Pressure	14,310 psi

CONNECTION PROPERTIES	
Connection Type	Premium Thread&Coupled
Nominal Connection OD	7.852 in
Nominal Connection ID	6.161 in
Make-up Loss	4.973 in
Coupling Length	11.929 in
Tension Efficiency	100% of Pipe Body
Compression Efficiency	60% of Pipe Body
Internal Pressure Efficiency	100% of Pipe Body
External Pressure Efficiency	100% of Pipe Body

JOINT PERFORMANCES	
Tensile Strength	1,272 klb
Compression Strength	763 klb
Internal Pressure Resistance	15,560 psi
External Pressure Resistance	14,310 psi
Maximum Bending	30 °/100 ft
Maximum Load on Coupling Face	1,016 klb

FIELD TORQUE VALUES	
Friction Coefficient	1
Min. Make-up torque	16,400 ft-lb
Opti. Make-up torque	18,230 ft-lb
Max. Make-up torque	20,000 ft-lb
Min. Shoulder torque	910 ft-lb
Max. Shoulder torque	14,580 ft-lb
Min. Delta Turn	0.010 turns
Max. Delta Turn	0.120 turns

Generated on 03/05/2026